

HzBeat

SPECIFICATIONS

Part's Number	HCCTA20T40G-B
Frequency(GHz)	2.0-4.0
Direction	Clockwise
Insertion Loss(dB)MAX	0.5(0.8)
Isolation(dB)MIN	17.0(15.0)
VSWR MAX	1.35(1.40)
Phase equalization($\pm^\circ$)	-
PK/CW (Watt)	-/80
Operating Temperature($^\circ\text{C}$)	-55~+85
Reverse Power(Watt)	-
Conector	SMA
Base plate plating	Thread Fastening
BW Max	FULL

Description:Coaxial Circulator

Description:Coaxial Isolator

Unit:mm

1:1

A4



SPECIFICATIONS

Part's Number	HCCTA20T40G-B
Frequency(GHz)	2.0-4.0
Direction	Clockwise
Insertion Loss(dB)MAX	0.5(0.8)
Isolation(dB)MIN	17.0(15.0)
VSWR MAX	1.35(1.40)
Phase equalization($\pm^\circ$)	-
PK/CW (Watt)	-/80
Operating Temperature($^\circ\text{C}$)	-55~+85
Reverse Power(Watt)	-
Conector	SMA
Base plate plating	Thread Fastening
BW Max	FULL

Description:Coaxial Circulator

Description:Coaxial Isolator



1:1

Unit:mm

A4