

1		2		3		4		5		6	
Document No.		REV		DWG BY		CHK'D BY		APPV'D BY		Date	
HD220530-5		0		Keith W							

SPECIFICATIONS	
Part's Number	HMITB330T370G-M
Frequency(GHz)	33.0-37.0
Direction	Counter Clockwise
Insertion Loss(dB)MAX	0.8
Isolation(dB)MIN	18
VSWR MAX	1.35
Phase equalization(±°)	-
PK/CW (Watt)	5/2
Operating Temperature(°C)	-55~+85
Reverse Power(Watt)	1
Conector	Gold wire bonding
Surface treatment	Gold Plating
Additional Notes	

Description:Microstrip Isolator

Hzbeat Electronic Technology Co. Ltd

10:1

Unit:mm

A4

SPECIFICATIONS		
Part's Number	HMITB330T370G-M	
Frequency(GHz)	33.0-37.0	
Direction	Counter Clockwise	
Insertion Loss(dB)MAX	0.8	
Isolation(dB)MIN	18	
VSWR MAX	1.35	
Phase equalization(±°)	-	
PK/CW (Watt)	5/2	
Operating Temperature(°C)	-55~+85	
Reverse Power(Watt)	1	
Conector	Gold wire bonding	
Surface treatment	Gold Plating	
Additional Notes		
Description:Microstrip Isolator		
Hzbeat Electronic Technology Co. Ltd		10:1
	Unit:mm	A4